

Pure Component Equations

Fitting of Pure Component Equation Parameters

DDBSP – Dortmund Data Bank Software Package



DDBST - Dortmund Data Bank Software & Separation Technology GmbH
Marie-Curie-Straße 10
D-26129 Oldenburg
Tel.: +49 441 361819 0
support@ddbst.com
www.ddbst.com

Contents

1 Introduction.....	3
2 List of Equations.....	4
3 Using the program.....	10
3.1 Initial Dialog.....	10
3.2 File Menu.....	11
3.3 ?-Menu.....	12
3.4 Component Selection.....	13
3.5 Check Data Availability.....	14
3.6 Fit.....	15
3.6.1 Input by Hand.....	16
3.6.2 Fit Results.....	17
3.6.3 Plot.....	18
4 Understanding the ParameterDDB Data Set Display.....	22
5 Working with a Parameter Data Set.....	23
5.1 Copy.....	23
5.2 Edit.....	24
5.3 Plot.....	25
5.4 Details.....	26
5.5 Calculate.....	27
6 Fit Archive.....	28
7 T _c /P _c Evaluation.....	29
8 Density Prediction by Equation of State.....	31
9 Virial Coefficients.....	32
9.1 Isotherms.....	32
9.1.1 Rationale.....	32
9.1.2 Application Flow.....	32
9.1.3 Description of the Graphics Output.....	32
9.1.4 Mathematical and Physical Relations.....	33
9.1.5 Practical Tips.....	35
9.1.6 Gas Constant, Molar Mass, Critical Density.....	35
9.2 All Data Simultaneously.....	35
9.2.1 Rationale.....	35
9.2.2 Problem Description.....	35
9.2.3 Regression.....	35
9.2.4 Short Tutorial.....	37
10 Volume Translation.....	40
11 Simultaneous Regression of α Function Parameters.....	42

1 Introduction

PCPEquationFit fits parameters for a large variety of equations for pure component properties. Parameters can be stored in and retrieved from a parameter database, they can be plotted, and they can be used for calculations.

PCPEquationFit normally uses the pure component properties data bank which is a part of the Dortmund Data Bank. It can also be used to fit data from other data sources since tables can be pasted from the clipboard or loaded from files.

2 List of Equations

<i>Property</i>	<i>Equation</i>
Liquid Viscosity T [K] η [mPa s]	1. Andrade $\eta = e^{A + \frac{B}{T}}$ 2. Vogel $\eta = e^{A + \frac{B}{T+C}}$ 3. DIPPR 101 $\eta = e^{A + \frac{B}{T} + C \ln T + DT^E}$ 4. PPDS 9 $\eta = E \exp \left[A \left(\frac{C-T}{T-D} \right)^{\frac{1}{3}} + B \left(\frac{C-T}{T-D} \right)^{\frac{4}{3}} \right]$ 5. Extended Andrade $\eta = e^{A + \frac{B}{T} + CT + DT^2 + ET^3}$ 6. Polynomial in 1/T $\eta = A + \frac{B}{T} + \frac{C}{T^2} + \frac{D}{T^3} + \frac{E}{T^4}$
Vapor Viscosity T[K] η [mPa s]	1. DIPPR 102 $\eta = \frac{AT^B}{1 + \frac{C}{T} + \frac{D}{T^2}}$ 2. Polynomial $\eta = A + B \cdot T + CT^2 + DT^3 + ET^4$

Property	Equation
Saturated Vapor Pressure T [K] P [kPa]	<p>1. Antoine $P=10^{A-\frac{B}{T+C}}$ (► Other Units: T [°C], P [mmHg])</p> <p>2. Wagner 2,5,5 $P=\exp\left(\ln P_c + \frac{A(1-T_r)+B(1-T_r)^{1.5}+C(1-T_r)^{2.5}+D(1-T_r)^5}{T_r}\right)$</p> <p>3. Wagner 3,6 $P=\exp\left(\ln P_c + \frac{A(1-T_r)+B(1-T_r)^{1.5}+C(1-T_r)^3+D(1-T_r)^6}{T_r}\right)$</p> <p>4. Cox $P=\exp\left[\ln 101.325+e^{A+B\left(\frac{T}{T_B}\right)+C\left(\frac{T}{T_B}\right)^2\left(1-\frac{T_B}{T}\right)}\right]$</p> <p>5. DIPPR 101 $P=e^{A+\frac{B}{T}+C\ln T+DT^E}$ (► Other Units: P [Pa])</p> <p>6. Extended Antoine (Lonza) $P=\exp\left(A+\frac{B}{T+C}+DT+ET^2+F\ln(T)\right)$ (► Other Units: P [bar])</p> <p>7. Extended Antoine (Aspen) $P=\exp\left(A+\frac{B}{T+C}+DT+E\ln(T)+FT^G\right)$ G=1 or G=2</p> <p>8. Extended Antoine (Hysys) $P=\exp\left(A+\frac{B}{T+C}+D\ln(T)+ET^F\right)$ F=1 or F=2</p> <p>9. Raey2P $P=P_{atm}10^{\left[(4.1012+A)\left(\frac{T-B}{T-\frac{B}{8}}\right)\right]}$ $B \approx T_b$ $-1 < A < +1$</p> <p>10. Xiang/Tan $P=P_c \cdot \exp\left(\ln T_R \cdot \left(A_1 + A_2(1-T_R)^{1.89} + A_3(1-T_R)^{5.67}\right)\right)$</p> <p>11. PVExpansion: $P=\exp\left(A+\frac{B}{T}+C\ln(T)+DT+ET^2+\frac{F}{T^2}+GT^6+\frac{H}{T^4}\right)$</p> <p>12. Hoffman/Florin: $P=\exp\left(A+B\left(\frac{1}{T}-7.9151 \cdot 10^{-3}+2.6726 \cdot 10^{-3} \cdot \log_{10}(T)-0.8625 \cdot 10^{-6} \cdot T\right)\right)$ (► Other Units: P [Pa])</p>

Property	Equation
Saturated Vapor Pressure by EOS T [K]	1. Mathias-Copeman Constants for EOS $\alpha = \left(1 + m \cdot (1 - \sqrt{T_r})\right)^2$ $m = c_1 + c_2 \cdot (1 - \sqrt{T_r}) + c_3 \cdot (1 - \sqrt{T_r})^2$
P [kPa]	2. Twu-Bluck-Cunningham-Coon Constants for EOS $\alpha = T_r^{(c_3 \cdot (c_2 - 1))} \cdot \exp\left(c_1 \cdot \left(1 - T_r^{(c_2 \cdot c_3)}\right)\right)$ (c_1, c_2, c_3 used in DDB programs) $\alpha = T_r^{(N \cdot (M - 1))} \cdot \exp\left(L \cdot \left(1 - T_r^{(M \cdot N)}\right)\right)$ (L, M, N like original authors)
	3. Melhem-Saini-Goodwin Constants for EOS $\alpha = \exp\left(c_1 \cdot (1 - T_r) + c_2 \cdot (1 - \sqrt{T_r})^2\right)$
	4. Stryjek-Vera Constants for EOS $\kappa = \kappa_0 + \kappa_1 \left(1 + \sqrt{T_r}\right) \left(0.7 - T_r\right)$ $\alpha = \left(1 + \kappa \left(1 - \sqrt{T_r}\right)\right)^2$
	5. Stryjek-Vera-2 Constants for EOS $\kappa = \kappa_0 + [\kappa_1 + \kappa_2 (\kappa_3 - T_r^{0.5}) (1 - T_r^{0.5})] [1 + T_r^{0.5}] (0.7 - T_r)$ $\alpha = \left(1 + \kappa \left(1 - T_r^{0.5}\right)\right)^2$
	6. Schwartzentruber/Renon/Watanasiri Constant for EOS $P_{rm} = 0.37464 + 1.54226 \cdot \omega - 0.26992 \cdot \omega^2$ $\alpha = \left(1 + P_{rm} \cdot \left(1 - \sqrt{T_r}\right) - \left(1 - \sqrt{T_r}\right) \cdot (c_1 + c_2 \cdot T_r + c_3 \cdot T_r^2)\right)^2$
Liquid Heat Capacity T [K] c_p [J/mol K]	1. Polynomial $c_p = A + BT + CT^2 + DT^3 + ET^4$ 2. PPDS 15 $c_p = R \left(\frac{A}{\tau} + C \tau + D \tau^2 + E \tau^3 + F \tau^4 \right)$ with $\tau = 1 - \frac{T}{T_c}$

Property	Equation
Ideal Gas Heat Capacity T [K] c_p [J/mol K]	<p>1. Polynomial $c_p = A + BT + CT^2 + DT^3 + ET^4$</p> <p>2. Aly-Lee, DIPPR 107 $c_p = a_0 + a_1 \left(\frac{a_2}{\sinh \frac{a_2}{T}} \right)^2 + a_3 \left(\frac{a_4}{\cosh \frac{a_4}{T}} \right)^2$</p> <p>3. PPDS 2 $C_p = R \left(B + (C - B) y^2 \left[1 + (y - 1) (D + E y + F y^2 + G y^3) \right] \right)$ with $y = \frac{T}{A + T}$</p> <p>4. Shomate $c_p = A + B T + C T^2 + D T^3 + \frac{E}{T^2}$</p> <p>5. Wilhoit</p> $\frac{c_p}{R} = A + \left(\frac{B}{T^2} \right) \cdot \exp \left(\frac{-C}{T} \right) + D \cdot y^2 + \left(E - \frac{F}{(T - H)^2} \right) \cdot y^8 \quad \text{with} \quad y = \frac{T - G}{T + F}$
Solid Heat Capacity T[K] c_p [J/mol K]	Polynomial $c_p = A + BT + CT^2 + DT^3 + ET^4$

Property	Equation
Liquid (Saturated) Density T [K] ρ [kg/m ³]	<p>1. DIPPR 105 $\rho = \frac{A}{B + \left(1 - \frac{T}{C}\right)^D}$</p> <p>2. Polynomial $\rho = A + B \cdot T + C T^2 + D T^3 + E T^4$</p> <p>3. Tait (pressure-dependent data) $P_{ref} = \max(f(T), 1.01325) \text{ MPa}$ (Wagner-Equation)</p> $\rho_{ref} = f(T) \frac{kg}{m^3}$ (DIPPR 105-Equation) $T_{reduced} = 100 \quad T_R = \frac{T}{T_{reduced}}$ $C = c_0 + c_1 T_R$ $B = b_0 + b_1 T_R + b_2 T_R^2 + b_3 T_R^3 + b_4 T_R^4$ $\rho = \frac{\rho_{ref}}{1 - C \ln \left[\frac{B + P}{B + P_{ref}} \right]}$ <p>4. DIPPR 116 (with additional addend ρ_c, the critical density)</p> $\rho_L = \rho_c + \left[A \tau^{0.35} + B \tau^{\frac{2}{3}} + C \tau + D \tau^{\frac{4}{3}} \right] \quad \text{with} \quad \tau = 1 - \frac{T}{T_c}$ <p>5. DIPPR 119</p> $\rho = A + B \cdot \tau^{\frac{1}{3}} + C \cdot \tau^{\frac{2}{3}} + D \cdot \tau^{\frac{5}{3}} + E \cdot \tau^{\frac{16}{3}} + F \cdot \tau^{\frac{43}{3}} + G \cdot \tau^{\frac{110}{3}} \quad \text{with} \quad \tau = 1 - \frac{T}{T_c}$
Surface Tension T [K] σ [N/m]	<p>1. Polynomial $\sigma = A + B T + C T^2 + D T^3 + E T^4$</p> <p>2. Short DIPPR 106 $\sigma = A (1 - T_R)^n$ with $T_R = \frac{T}{T_c}$</p> <p>3. $\sigma = A (T - T_c)^B$</p> <p>4. Full DIPPR 106 $\sigma = A (1 - T_r)^{B + C T_r + D T_r^2 + E T_r^3}$ with $T_r = \frac{T}{T_c}$</p> <p>5. PPDS 14 $\sigma = A \cdot \tau^B \cdot (1 + C \cdot \tau)$ with $\tau = 1 - \frac{T}{T_c}$</p>

Property	Equation
Second Virial Coefficient T [K] B_{ii} [cm ³ /mol]	1. $B_{ii} = \frac{A}{\sqrt{T}} + \frac{B}{T}$ 2. DIPPR 104 $B_{ii} = A + \frac{B}{T} + \frac{C}{T^3} + \frac{D}{T^8} + \frac{E}{T^9}$
Heat of Vaporization T [K] H_{vap} [J/mol]	1. DIPPR 106 $H_{Vap} = A \left(1 - \frac{T}{T_c}\right)^{B+C\left(\frac{T}{T_c}\right)+D\left(\frac{T}{T_c}\right)^2+E\left(\frac{T}{T_c}\right)^3}$ 2. Extended Watson $H_{Vap} = a(c-T)^b + d$ 3. PPDS 12 $H_{Vap} = R T_c \left(A \tau^{\frac{1}{3}} + B \tau^{\frac{2}{3}} + C \tau + D \tau^2 + E \tau^6\right)$ with $\tau = 1 - \frac{T}{T_c}$ 4. Pitzer/Carruth/Kobayashi $H_{vap} = A \cdot \tau^{\frac{1}{3}} + B \cdot \tau^{\frac{2}{3}} + C \cdot \tau$ with $\tau = 1 - \frac{T}{T_c}$
Liquid Thermal Conductivity T [K] λ [W/m K]	1. Polynomial $\lambda = A + BT + CT^2 + DT^3 + ET^4$ 2. PPDS 8 $\lambda = A \left(1 + B \tau^{\frac{1}{3}} + C \tau^{\frac{2}{3}} + D \tau\right)$ with $\tau = 1 - \frac{T}{T_c}$
Vapor Thermal Conductivity T [K] λ [W/m K]	1. PPDS 3 $\lambda = \frac{\sqrt{T_r}}{A + \frac{B}{T_r} + \frac{C}{T_r^2} + \frac{D}{T_r^3}}$ with $T_r = \frac{T}{T_c}$
Isothermal Compressibility	Linear Interpolation
Thermal Expansion Coefficient	Linear Interpolation
Melting Temperature (Pressure Dependency)	Simon-Glatzel Equation $P_m = a \left(\left(\frac{T_m}{T_{m(normal)}} \right)^c - 1 \right)$
Dielectric Constants of Liquids, Permittivity T K], ϵ [.]	1. Polynomial $\lambda = A + BT + CT^2 + DT^3 + ET^4$

3 Using the program

3.1 Initial Dialog




Figure 1: Main PCPEquationFit Dialog

The program's start dialog contains three major parts:

1. The components area allows
 1. selecting components
 2. displaying component details with the component editor
 3. displaying the content of the Dortmund Data Bank for the selected component
 4. verifying if enough data sets or points are available (this is only a hint, since there might be further constraints)
2. The list of equations. The list is organized hierarchically. The methods are summarized below the property they describe.
3. The parameter data set shows the current content of the ParameterDDB.



3.2 File Menu

- **Open Component Numbers File**

This function allows loading a file with a list of DDB component numbers. Such component files can be created, for example, in the component selection dialog or in the main Dortmund Data Bank program from search results. The data set numbers are shown in a separate window.

Component Numbers	
Components	
#DDB	Name
3	Acetonitrile
4	Acetone
8	1,2-Ethanediol
11	Ethanol
12	Diethyl ether
21	Ethyl acetate
31	Benzene
39	1-Butanol
47	Chloroform

30 components




Figure 2: File menu

A click on a line sets the component number in the main fit window.

- **Count**

Count shows the number of available parameter data sets for the current model.




Figure 3: Parameter Data Set Count

- **Statistics**

Statistics creates a table with an overview over all equations

Statistics						
Equation ID	Count	Systems/Components	Equation Short Term	Property	Description	^
1	82	82	EOS-MR	Vapor-liquid Equilibria	Equation of State	
2	732	680	WAG25	PCP - Saturated Vapor Pressures	Wagner Equal	
3	15	14	WAG36	PCP - Saturated Vapor Pressures	Wagner Equal	
4	8026	6851	ANT	PCP - Saturated Vapor Pressures	Antoine Equat	
5	914	914	COX	PCP - Saturated Vapor Pressures	Cox Equation	▼

Figure 4: Statistics

- Database Details (Current Equation)**

This function creates a table with all data sets available for the current equation.

Mathias-Copeman Equation for Soave-Redlich-Kwong EOS

Minimum data points: 4 Build List

Minimum T range: 75 K

#	Component	T min exp. Data	T max exp. Data	Sets exp. Data	Points exp. Data	References exp. Data
1	1	176.150	382.900	51	158	49
2	2	358.200	495.150	10	15	10
3	3	273.150	535.032	196	678	192
4	4	168.400	508.650	434	1326	417

3339 components with sufficient data but without parameters found.

Save Component List Use As Component List

Only components where Tc and Pc are available

Figure 5: Database Details (Current Equation)

- Database Overview**

This function creates a table with the number of components for experimental data in the Pure Component Properties part of the Dortmund Data Bank are available for the single equations.

Scanning PCP Database: 336719 of 365483

#	Equation	Component	Description	
1	2	5842	Wagner	PCP -
2	3	5842	Wagner	PCP -
3	4	7236	Antoine	PCP -
4	5	6372	Cox	PCP -
5	20	5842	DIPPR	PCP -

Figure 6: Database Overview

- Archive**

See chapter “Fit Archive” on page 28.

- ParamDBOrganizer**

This function calls the program for managing the parameter data base. This program is described in a separate PDF (“ParameterDDBOrganizer.pdf”).

- Build ParameterDB Index**

This will rebuild the component index of the parameter data base. This is normally done automatically when needed. This function is only needed if changes outside PCPEquationFit have been made.

3.3 ?-Menu

The help menu contains a button which brings this PDF help up and an “About” button which shows some information about the program.



Figure 7: Help menu

3.4 Component Selection

DDB component numbers can be typed directly in the left component field. After a *Return* the component name is added.

The buttons allow to navigate through the DDB component list.

The button calls the component selection dialog





Figure 8: Component Selection


which is described in details in other documents.

3.5 Check Data Availability

 Check Data Availability

This button starts a search in the pure component property data bank for experimental data for the currently selected equation.

When this search is finished the “Check Data Availability” is hidden and information about the availability of data is shown.



The information lines shows for how many components the Dortmund Data Bank contains experimental data sets. The example shows the number of components for the Antoine equation (saturated vapor pressures).

Clicking on the underlined label (“Components 7196”) will open a window with the list of components.

The “Data are available” line indicates that there are enough data points for the specific equation. This number is normally set to <number of parameters + 1>.

If no data are available this text will be displayed: **No data available.**

The check box  **Only components with PCP data** should be used in “walk-through” mode where a list of components is in work. If checked this will avoid the display of components without experimental data points.

A detailed description of all component selection features is available in the “Component Management” documentation.

Component Numbers	
Components	
#DDB	Name
1	Acetaldehyde
2	Acetamide
3	Acetonitrile
4	Acetone
5	Ethylenediamine
6	1,2-Dibromoethane
7	Ethyl bromide
8	1,2-Ethanediol
9	Ethyl iodide
10	5-Ethyl-2-nonanol
11	Ethanol
12	Diethyl ether

3.6 Fit

After the component and the equation has been selected and the program indicates that enough data points are available (Data are available) the *Fit* button displays a model specific dialog with almost the same content for the different models.



The used example for showing a typical fit is the Wagner 2.5-5 equation for saturated vapor pressures.





Figure 9: Fit Dialog for Wager 2.5-5 equation

The dialog displays the data source – which is in most cases the pure component properties data bank. All possible sources are



The dialog displays the number of available data points and the number of different references (number of different authors) and repeats the display of the component name. The two buttons besides the name invoke the component editor and the Dortmund Data Bank program.

The temperature and pressure range are also displayed. These limits are editable and can be used to cut points by increasing the lower limit or decreasing the upper limit. The knife button will actually throw the points outside the given ranges away. The “Edit Data Points” allows to modify the data from the data sources. It uses the “Input by Hand” dialog.

The normal boiling point (T_b), the critical data (T_c , P_c , ρ_c), and the melting point (T_m) are read from pure component basic files (not from the pure component properties data bank).

The lower part of the dialog is model specific but contains in most cases starting parameters and a selection for an objective function where appropriate.

3.6.1 Input by Hand

If this input mode is selected a dialog with a data grid is shown where the user can either type or paste or load data.

T [K]	P [kPa]

Figure 10: Input by Hand

3.6.2 Fit Results

After pressing the *Fit* button the fit will start and present a “New Parameters” box when it's finished:




Figure 11: Fit Result

This box shows the new parameters, a mean error, the used temperature limits, the data source and the current date and in some cases additionally used constants like in this example T_c and P_c .

These entries will be stored in the ParameterDDB if one of the “Save” buttons will be pressed.

3.6.3 Plot

For an overview on the fit quality PCPEquationFit provides several plots.




Figure 12: Plot – Fit Result

The list of plots slightly varies from model to model. Always the same is the rubber band drawn from the mouse cursor to the nearest point. Detailed information of this point are displayed in the status line. Additionally the reference is shown below the tool bar.

The “Experimental Data” button adjusts the diagram so that the experimental data are filling the chart window.



This is useful in the cases where critical data and melting points are shown and the experimental data are available only for a smaller range. The “Exact” button restores the original diagram so that all data are shown.



Figure 13: "Exact"




Figure 14: "Experimental Data"

Through a context menu on the plot it is possible to.




Figure 15: Plot Context Menu


Additionally a complete list of deviations can be created (“Table of Deviations” tool button) and the diagram can be copied to the Windows clipboard or printed.

Grid Output							
Print Copy Save Mail							
Grid Output							
Dataset	Temperature [K]	Pressure [kPa] (Exp.)	Pressure [kPa] (Calc.)	Deviation	Relative Deviation [%]	Used	^
19640	153.35	0.00035997	0.0001465825	-0.0002133875	-59.28	Yes	▼
19640	155.85	0.0008665956	0.000240541	-0.000626055	-72.24	Yes	▼
19637	160.35	0.000687944	0.000559732	-0.000128212	-18.64	Yes	▼
19637	163.15	0.00108258	0.0009200832	-0.0001624968	-15.01	Yes	▼
19640	168.45	0.00266645	0.002231031	-0.0004354188	-16.33	Yes	▼

Figure 16: Table of Deviations

The “Data Points” tool button opens a dialog where all data points are listed. This dialog can be used to include and exclude data points.

This function has been added because of points occupying exactly the same position (exactly same data) which makes it impossible to select all these points by mouse.



The screenshot shows a Windows-style dialog box titled "Data Points". At the top left is a small icon of a document with a blue border. Below the title bar is a toolbar with a "Update Plot" button (a blue square with a white plot icon) and a "Refit" button (a blue square with a calculator icon). The main area is a table with the following columns: "Use?", "x", "y", "#Ref", "#Set", "Quality", and "Reference". There are seven rows of data, each with a checked checkbox in the "Use?" column. The "x" column contains values like 153.350, 155.850, etc., and the "y" column contains values like 0.00035997, 0.000866596, etc. The "Reference" column lists "[50702] Drucker C., Jimeno E., Kangro W., Z.Phys." repeated seven times.

Use?	x	y	#Ref	#Set	Quality	Reference
<input checked="" type="checkbox"/>	153.350	0.00035997	50702	19640	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	155.850	0.000866596	50702	19640	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	160.350	0.000687944	50702	19637	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	163.150	0.00108258	50702	19637	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	168.450	0.00266645	50702	19640	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	169.150	0.00253313	50702	19637	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.
<input checked="" type="checkbox"/>	171.550	0.00586619	50702	19640	0	[50702] Drucker C., Jimeno E., Kangro W., Z.Phys.

Figure 17: Data Points Selection

If points have been excluded it is necessary to start a new fit by the Refit button. This will return us to the fit dialog allowing to store the modified parameters.

4 Understanding the ParameterDDB Data Set Display


Key	Value
A	-7.19274
B	1.13092
C	-1.56552
D	-5.98843
C1	12
Pc	3637.6
Tc	466.7
EQID	2
Tmax	467.05
Tmin	153.35
User	
COUNT	1
DateD	2
DateM	5
DateY	
Error	0.37598
SETPNUM	2
Source	PCP
LOCATION	1
AUTOSELECT	true

The ParameterDDB contains key/value pairs. The keys describe the values. The grid shows the list of keys and the values belonging to them.

1. The keys “A”, “B”, “C”, “D” and so on are the parameters of the equations.
2. “C1” is the DDB component number. Its name can be found in the component editor.
3. “Pc”, “Tc” are critical temperature and pressure. Other possible entries are e.g. “Tb”.
4. “EQID” is the internal equation number.
5. “Tmax” and “Tmin” are the upper and lower temperature limits of the experimental data used. Please regard these values also as validity range for the equation.
6. “User” specifies the person who stored the parameter data set.
7. “DateD”, “DateM”, “DateY” specify the date when the data set has been stored.
8. “Error” gives the model and fit specific error.
9. “Source” specifies the source of the data points which have been used for the fit.
10. “Location” specifies if the parameter set is stored in the public DDB (0) or in the private DDB (1) or, if missing or another number, some other location.
11. “AUTOSELECT” is necessary if more than one data set is available for a component and a single equation. It specifies the preferred parameter set.


Figure 18: Parameter Data Set

5 Working with a Parameter Data Set



5.1 Copy


The data set grid will be copied to the windows clipboard as it is displayed in Figure 18 (source) and Figure 19 (destination).



Three formats are supported:

1. “Copy as Table” with key and value separated by tab.
This is useful for pasting the content into a spreadsheet.
2. “Copy as Text (Full)” with key and value separated by the equation sign (“=”). This is a useful format for pasting into text processors.
3. “Copy as Text (Short) with key and value separated by the equation sign (“=”) but limited to parameters and validity limits. This is a useful format for pasting into mails.

The Copy function are also available in a context menu of the parameter grid.



	A	B	
1	Key	Value	
2	A	70.136	
3	B	0.256971	
4	C	507	
5	D	0.28571	
6	C1	459	
7	EQID	9	
8	Tmax	506	
9	Tmin	209.15	
10	COUNT	1	
11	Error	9.16E-05	
12	DCnt	1	


Figure 19: Data set pasted in spreadsheet

5.2 Edit

The editor is another view on the parameter data set grid. The grid is now editable and new values can be typed in the Value column.

The Key column is not directly editable but new keys ( **New Key**) can be added and keys with empty values will be removed automatically when the data set is saved.

The “Recommended Value” check mark should be set if more than one data set is available for the same component and equation and the current data set should be preferred over all others.



The screenshot shows a Windows-style application window titled "Edit". At the top, there are standard window controls: a blue title bar with the title "Edit", a red "X" button, a yellow "Save" button, and a green "Minimize" button. Below the title bar is a toolbar with a "Save" icon. The main area contains a "Dataset Number" field with the value "60999" and a "Location" field with the value "Private DDB". Below these fields is a table with two columns: "Key" and "Value". The table contains eight rows with the following data:

Key	Value
A	-7.19509
B	1.14438
C	-1.60749
D	-5.86095
Pc	3637.6
Tc	466.7
Tmax	467.05
Tmin	153.35

At the bottom of the window, there is a "Recommended Value" checkbox which is checked, and a "Yes" button next to it. There is also a "New Key" button with a key icon.

Figure 20: Data set editor

5.3 Plot

This plot shows the stored equation parameters together with points from the pure component properties data bank. It's the same plot as used in the fit procedure with the exception that some editing functions are not available – like removal of data points.




Figure 21: Plot output

5.4 Details

This function displays a more detailed and explanatory view on the current parameter set. It is part of the ParamDDBOrganizer program.




Figure 22: Data set details

This program is described in detail in the separate document “ParameterDDBOrganizer.pdf”.

5.5 Calculate

Stored parameter sets can be used to calculate the property at arbitrary temperatures.

It is either possible to calculate values in a temperature range where start and end temperature as well as a step width can be specified

Start Temperature 153.35	K	End Temperature 467.05	K	Stepwidth 1.00	K	<input type="button" value="Calculate"/>
-----------------------------	---	---------------------------	---	-------------------	---	--

or single values typed in the data grid.

Temperature	Cal
280	
285	
290	

Calculation

Dataset Information
Number: 60999 Location: Private

Start Temperature End Temperature Stepwidth
153.35 K 467.05 K 1.00 K

Temperature [K]	Calculated Value [kPa]
153.35	0.0001465825413
154.35	0.0001791172335
155.35	0.0002181915786
156.35	0.0002649794113
157.35	0.0003208389867

Figure 23: Calculate properties with stored parameters

6 Fit Archive


PCPEquationFit stores a history of fitted parameters and used data sets. This archive is accessible through the tool bar button  **Archive**.

The archive is intended to be the memory of all fits. It should allow to save the data which have been used for the fit and to restore them and perform a full re-fit under the same conditions as done originally. This goal is currently not perfectly achieved.

The archive dialog itself (Figure 24) shows a list of parameter sets identified by component number and model description separated for the public and private data banks.

The details grid shows the x and y, the reference number and the data set number and in the “Used” column a “+” if the value has been used in the fit or a “-” if the point has been excluded.


The “Refit” button creates a fit dialog for the given equation and component with the stored data points (Figure 25).



The screenshot shows the 'Archived Data' dialog. On the left, there's a list of entries with columns for #, Comp., and Model. The entry at index 7 is selected, showing details: Component 12, Model 'Vapor Pressure Wagner', Equation number 2, and Start values: -8.4.5.1. Below this is a detailed data grid with columns for Number, x, y, Ref., Dataset, and Used. The data points listed are:

Number	x	y	Ref.	Dataset	Used
1	1.533500E+2	3.599700E-4	50702	19640	+
2	1.558500E+2	8.665960E-4	50702	19640	+
3	1.603500E+2	6.879440E-4	50702	19637	+
4	1.631500E+2	1.082580E-3	50702	19637	+
5	1.684500E+2	2.666450E-3	50702	19640	+
6	1.691500E+2	2.533130E-3	50702	19637	+
7	1.715500E+2	5.866190E-3	50702	19640	+

Figure 24: Fit archive



The screenshot shows the 'Vapor Pressure - Wagner 2.5-5' refit dialog. At the top, it shows 'Data Source' as 'Archive'. Below that is a table for 'Points', 'Ref's', and 'Component' (set to 125 Diethyl ether). Under 'Temperature Range' and 'Dependent Value Range', there are two ranges: 153.35-467.05 and 0.00035997-3657.83. There are buttons for 'Edit Data Points' and 'Delete'. Below this are input fields for 'Tb [K]', 'Tc [K]', 'Pc [kPa]', 'Tm [K]', and 'pc [kg/m³]' with dropdown menus for units. Under 'Start parameters:', there is a text input field containing '-8.4.-5.1.' and a dropdown menu for the equation: 'F=Sum((yexp-ycal)/(syabs+syrel+sxabs*dydx)^2)' with parameters $\sigma_T = 0.01K$ and $\sigma_P = 0.5\%$.

Figure 25: Refit with archived data

7 T_c/P_c Evaluation

PCPEquationFit allows with this function the evaluation of experimental pure component critical data and saturated vapor pressures together with calculated and estimated values.

For a full investigation it is necessary to have at least a parameter set for a vapor pressure equation and the Artist program package should also be present since it is used for displaying estimated critical data.




Figure 26: Critical Data Evaluation - Plot




Figure 27: Critical Data Evaluation - Vapor Pressure Equations

The “Options” page allows selecting vapor pressure equations from PCPEquationFit and T_c and P_c estimation




Figure 28: Zoomed in for Critical Point


methods from Artist.

The resulting diagram shows all experimental, calculated, and estimated data points in a Temperature vs. Pressure plot. Deviations are shown in the same diagram with its scale on the diagram's right side.

The diagram allows switching between “T vs. P” and “ $1000/T$ vs. $\log_{10} P$ ” and the display of the deviations can be switched on and off.

The important point is the end point of the vapor pressure curve. The experimental and estimated critical T_c and P_c are shown as horizontal and vertical line. The intersections give a hint where the correct critical point lies.

8 Density Prediction by Equation of State



This dialog




Figure 29: Density Prediction

can be used to calculate liquid and vapor densities and volumes of pure components by equation of states. The supported equations of state are the same which can be used to regress α function parameters in the main dialog and the regressed α function parameters are used also for this density calculation.

Input for the calculation by the equation of state are temperatures and pressures. The pressure can either be given directly or the saturated vapor pressure can be used. The saturated vapor pressure would be determined by the equation of state.

Temperature [K]	Pressure [kPa]
450	2820.859192
475	4106.520926
422	1764.635871

Figure 30: Using saturated vapor pressures

9 Virial Coefficients

Original Author: Romana Laznickova

9.1 Isotherms

9.1.1 Rationale

The sub program ISOTHERM calculates second and third virial coefficients from qualified isothermal gas-phase PVT-data. The program also allows to compare the data sets and judge their quality.

9.1.2 Application Flow

The program allows either to load a pure component properties file containing PVT data or searches the datasets itself after a component has been selected.

The data from this list are sorted by temperature and data points measured at the same temperatures are collected and combined in isotherms.

These isotherms are searched for applicable data. For the calculation of virial coefficients only data up to $\frac{3}{4}$ of the critical density are used. Near the critical isotherm, at reduced temperatures between $T_r=0.95$ and $T_r=1.2$, only data with densities up to $\frac{1}{2}$ of the critical density are used. If an isotherm has at least two data points in the specified range it will be used to regress the second and third virial coefficients.

The virial coefficients are regressed by an optimizing algorithm which minimizes the sum of the squared errors of the compressibility factor. The quality of the optimization can be judged by the absolute and relative deviation in the compressibility factor and the density of the regressed virial equation from the experimental values. The regression quality is also characterized by the numbers square root from the mean squared error of the compressibility factor and the density. Additionally the program determines a maximum pressure (P_{maxB}), which gives a real density value for a virial equation made up only with the second coefficient B .

The results are listed on screen giving an overview over all temperatures. Regression results are given for all temperatures where experimental data points have been available. The experimental datasets are listed together with the regressed second and third virial coefficients, the maximum pressure (P_{maxB}), the absolute and relative density deviation and both characterization numbers.

9.1.3 Description of the Graphics Output

The main chart is the display of $\frac{\text{Compressibility Factor} - 1}{\text{Density}}$ against the density. The virial equation build

with B and C is a straight line in this case. The axis intercept on the y-axis is the second virial coefficient B and slope of the straight line is the third virial coefficient C . This projection allows evaluating the quality of the optimization in a very clear way. For isotherms where B and C have been obtained a calculated line is included.

There are four other charts which display differences between the experimental values and the correlation:

1. Absolute deviation in the density,
 2. Relative deviation in the density,
 3. Absolute deviation in the compressibility factor,
 4. Relative deviation in the compressibility factor
- against the density.

The chart also includes the critical density.

9.1.4 Mathematical and Physical Relations

9.1.4.1 Display of Compressibility Factor-1 against Density

This presentation is based on the relation for second virial coefficient

$$B = \lim_{d \rightarrow 0} \left(\frac{z-1}{d} \right)$$

and the third virial coefficient

$$C = \lim_{d \rightarrow 0} \left(\frac{\partial \left(\frac{z-1}{d} \right)}{\partial d} \right)$$

The equation evolved up to the third virial coefficient

$$z = 1 + B \cdot d + C \cdot d^2$$

is a straight line in the presentation of $\frac{\text{Compressibility Factor}-1}{\text{Density}}$ against density.

$$\frac{z-1}{\rho} = B + C \cdot \rho$$

Because virial coefficients are normally shown in molar units (B [$\text{cm}^3 \cdot \text{mol}^{-1}$], C [$\text{cm}^6 \cdot \text{mol}^{-2}$]) and densities in [$\text{kg} \cdot \text{m}^{-3}$] the ordinate shows $\frac{\text{Compressibility Factor}-1}{\text{Density}}$ in [$\text{cm}^3 \cdot \text{mol}^{-1}$] and the abscissa shows densities in [$\text{kg} \cdot \text{m}^{-3}$]. If the third virial coefficient shall be determined graphically from this presentation it is necessary to convert both units.

9.1.4.2 Optimization

The optimization routine searches for a combination of the second and third virial coefficients where the sum of squares of errors of the compressibility factor is minimal.

$$F = \sum_i (z_i - z_{\text{calc},i})^2 \stackrel{!}{=} \text{Min}$$

i runs over all experimental data points for a specified isotherm. The compressibility factor z_i is calculated from the measured temperature T , pressure P_i , and density ρ_i .

$$z_i = \frac{P_i \cdot M}{\rho_i \cdot R \cdot T}$$

The virial equation calculates the compressibility factor $z_{\text{calc},i}$ for the experimental density ρ_i

$$z_{\text{calc},i} = 1 + B' \cdot \rho_i + C' \cdot \rho_i^2$$

with

$$B' = \frac{B}{M} \quad \text{and} \quad C' = \frac{C}{M^2} \qquad \text{Equation 8}$$

The minimum of the objective function $F=F(B',C')$ is determined mathematically exact. The necessary condition for a minimum is the existence of a combination of the second and third virial coefficients that the partial derivations of the objective function by B' and C' are zero.

$$\frac{\partial F}{\partial B'}=0 \quad \text{and} \quad \frac{\partial F}{\partial C'}=0$$

These conditions lead to linear equation system.

$$\sum_i \frac{P_i M}{R \cdot T} - \rho_i - B' \cdot \sum_i \rho_i^2 - C' \cdot \sum_i \rho_i^3 = 0$$

$$\sum_i \frac{P_i M \cdot \rho}{R \cdot T} - \rho_i^2 - B' \cdot \sum_i \rho_i^3 - C' \cdot \sum_i \rho_i^4 = 0$$

This equation system is solved by the Gauß-Jordan method. The results are the second and third virial coefficients B' and C' in mass units. These values are converted by equations (8) into molar units. The program displays the second virial coefficient in $\text{cm}^3 \cdot \text{mol}^{-1}$ and the third in $\text{cm}^6 \cdot \text{mol}^{-2}$.

9.1.4.3 Evaluation of the Optimization Quality

The goodness of the optimization can be evaluated by the difference between the experimental values and the calculated values.

- absolute deviation in the density

$$\rho_i - \rho_{calc,i}$$
- relative deviation in the density

$$\frac{\rho_i - \rho_{calc,i}}{\rho_i} \cdot 100.$$
- absolute deviation in the compressibility factor

$$z_i - z_{calc,i}$$
- relative deviation in the compressibility factor

$$\frac{z_i - z_{calc,i}}{z_i} \cdot 100.$$

These deviations are determined for all experimental values.

Additional quality numbers are square root from the mean squared error of the compressibility factor

$$\sqrt{\sum_i \frac{(z_i - z_{calc,i})^2}{n}}$$

and the square root from the mean squared error of the density

$$\sqrt{\sum_i \frac{(\rho_i - \rho_{calc,i})^2}{n}}$$

These number are obtained only from the experimental values used in the optimization. n is the number of these values.

9.1.4.4 Pressure P_{maxB}

A virial equation with only B is quadratic against the density. If the second virial coefficient is negative, it depends on the pressure if the quadratic equation yields real solutions for the density. The pressure P_{maxB} is the maximum pressure where the equation with only B yields a real solution.

$$P_{maxB} = -\frac{R \cdot B}{4 \cdot B}$$

9.1.5 Practical Tips

This program only calculates virial coefficients from measured values in a reasonable range, despite this statement it is still necessary to carefully evaluate the results.

- Experimental values might be distributed only in a narrow range which might lead to an arbitrary result depending on scattering.
- If the densities are very small the experimental error will increase.

9.1.6 Gas Constant, Molar Mass, Critical Density

This program uses the gas constant $R = 8.3144 \frac{J}{K \cdot mol}$. The molar mass and the critical density are taken from the DDB file STOFF.

9.2 All Data Simultaneously

9.2.1 Rationale

The simultaneous correlation can be used for the evaluation of PVT data sets, especially for non-isothermal data (see previous section 9.1 “Isotherms” for isothermal data). Additionally the program allows the user to select data sets and interpolation between different data. The implemented virial equation regresses the second and third virial coefficient and uses a two-parameter temperature relation. Therefore the correlation needs at least four points in a system.

9.2.2 Problem Description

The correlation is a three-dimensional problem. T_i , P_i , ρ_i are lying on a surface. This surface has to be described by the virial equation with second and third coefficient and a two-parameter temperature function. Because it is hard to obtain meaningful three-dimensional graphical displays the program uses a projection of the $P\rho T$ space to the $P\rho$ (pressure against density) plain. The virial equation is drawn as a series of isothermal $P=f(\rho)$ curves.

9.2.3 Regression

The objective function is

$$F = \sum_i (z_i - z_{calc,i})^2 \rightarrow \text{Min} \quad \text{with} \quad z = \frac{P_i \cdot M}{\rho \cdot R \cdot T_i}$$

The virial equation is

$$z_{calc,i} = 1 + B_i \left(\frac{\rho_i}{M} \right) + C_i \left(\frac{\rho_i}{M} \right)^2 \quad \text{with } M [\text{kg/mol}], B [\text{m}^3/\text{mol}], C [\text{m}^6 * \text{mol}^{-2}]$$

The two-parameter temperature dependence for the second virial coefficient B is

$$B_i = \frac{b_1}{T_i^{0.5}} + \frac{b_2}{T_i}$$

Two-parameter temperature dependence for the third virial coefficient C is

$$C_i = \frac{c_1}{T_i^{1.2}} + \frac{c_2}{T_i^{10}}$$

The exact mathematical solution ($\frac{\partial F}{\partial b_1} = 0, \frac{\partial F}{\partial b_2} = 0, \frac{\partial F}{\partial c_1} = 0, \frac{\partial F}{\partial c_2} = 0$) leads to the linear equation system:

$$A_{11} \cdot x_1 + A_{12} \cdot x_2 + A_{13} \cdot x_3 + A_{14} \cdot x_4 = D_1$$

$$A_{21} \cdot x_1 + A_{22} \cdot x_2 + A_{23} \cdot x_3 + A_{24} \cdot x_4 = D_1$$

$$A_{31} \cdot x_1 + A_{32} \cdot x_2 + A_{33} \cdot x_3 + A_{34} \cdot x_4 = D_1$$

$$A_{41} \cdot x_1 + A_{42} \cdot x_2 + A_{43} \cdot x_3 + A_{44} \cdot x_4 = D_1$$

with

$$b_1 = x_1, b_2 = x_2, c_1 = x_3, c_2 = x_4$$

$$A_{11} = \frac{1}{M^2} \cdot \sum_i \frac{\rho_i^2}{T_i} \quad A_{12} = \frac{1}{M^2} \cdot \sum_i \frac{\rho_i^2}{T_i^{1.5}} \quad A_{13} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{1.7}} \quad A_{14} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{10.5}}$$

$$A_{21} = \frac{1}{M^2} \cdot \sum_i \frac{\rho_i^2}{T_i^{1.5}} \quad A_{22} = \frac{1}{M^2} \cdot \sum_i \frac{\rho_i^2}{T_i^2} \quad A_{23} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{2.2}} \quad A_{24} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{11}} \quad 7$$

$$A_{31} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{1.7}} \quad A_{32} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{12.2}} \quad A_{33} = \frac{1}{M^4} \cdot \sum_i \frac{\rho_i^4}{T_i^{2.4}} \quad A_{34} = \frac{1}{M^4} \cdot \sum_i \frac{\rho_i^4}{T_i^{11.2}}$$

$$A_{41} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{10.5}} \quad A_{42} = \frac{1}{M^3} \cdot \sum_i \frac{\rho_i^3}{T_i^{11}} \quad A_{43} = \frac{1}{M^4} \cdot \sum_i \frac{\rho_i^4}{T_i^{11.2}} \quad A_{44} = \frac{1}{M^4} \cdot \sum_i \frac{\rho_i^4}{T_i^{20}}$$

$$D_1 = \sum_i \left(\frac{P_i}{R \cdot T_i^{1.5}} - \frac{\rho_i}{T_i^{0.5} \cdot M} \right)$$

$$D_2 = \sum_i \left(\frac{P_i}{R \cdot T_i^2} - \frac{\rho_i}{T_i^{0.5} \cdot M} \right)$$

$$D_3 = \sum_i \left(\frac{P_i}{M \cdot R \cdot T_i^{2.2}} - \frac{\rho_i^2}{T_i^{1.2} \cdot M} \right)$$

$$D_4 = \sum_i \left(\frac{P_i}{M \cdot R \cdot T_i^{11}} - \frac{\rho_i^2}{T_i^{10} \cdot M} \right)$$

This equation system is solved by the Gauß-Jordan method. The results are

$$b_1 [m^3 \cdot mol^{-1} \cdot K^{0.5}]$$

$$b_2 [m^3 \cdot mol^{-1} \cdot K]$$

$$c_1 [m^6 \cdot mol^{-2} \cdot K^{1.2}]$$

$$c_2 [m^6 \cdot mol^{-2} \cdot K^{10}]$$

On screen the values are multiplied by 10^6 for b_1 and b_2 , and 10^{12} for c_1 and c_2 ($m \Rightarrow cm$).

9.2.4 Short Tutorial




Figure 31: Start Screen

Start Screen, Figure 31, shows the start screen. The PVT data are obtained from the DDB pure component properties database for the selected component. Now the program display the ranges in density, pressure, and temperature and allows the user to set new limits.




Figure 33: Pressure Limits




Figure 34: Temperature Limits


After the dialogs have been committed the program immediately regresses the virial coefficients and displays a result. The result list gives

1. name of component with its molecular weight,
2. number of points given and used,
3. the experimental values either from file or database,
4. used temperature, pressure, and density limits,
5. the regressed b_1 , b_2 , c_2 , c_3 values,
6. examples if the B and C at 353 K,
7. a table with experimental and calculated data,
8. error numbers for specifying the quality of the regression.

The plot output displays six charts.

1. normal plot (no isotherms)
2. B against T
3. C against T
4. relative compressibility factor deviation
5. compressibility factor deviation
6. relative density deviation
7. density deviation
8. normal plot: P against molar density

The plot output has a context menu (see Figure 35) which allows to display the experimental data in the database retrieval program or all the data coming from a single reference or some component details.



Additionally it allows to select data from a single reference for correlation. In this case the program re-correlates b_1 , b_2 , c_1 , c_2 only from this reference's data sets.

The chart contains some additional lines which are the critical density, 0.5 and 0.75 of the critical density, a zero line and the critical pressure, if the ordinate shows pressure values.

Figure 35: Plot context menu

10 Volume Translation

VTPR uses a volume translation based on the difference between the experimental volume and the volume calculated by the Peng-Robinson equation of state at $T=T_c \cdot 0.7$. This temperature is normally quite close to the normal boiling point. PSRK normally does not use a volume translation for the Redlich-Kwong EOS but it can use such a correction, in principle.




Figure 36: Volume Translation - Calculation

In this dialog the volumes calculated by the equations DIPPR 105, DIPPR 116, or Polynomial. The left table shows the calculation result with the volume translation value c in light green.

-4.13847

Density Equation
 DIPPR 105
 DIPPR 116
 Polynomial

The right table shows the already stored values in the parameter data bank.

The “Diagram” page shows the different calculated volume ($1/\rho$) curves, a vertical line at $T_c \cdot 0.7$ and experimental values from the pure component property data base.




Figure 37: Volume Translation - Diagram

11 Simultaneous Regression of α Function Parameters

A simultaneous fitting tool for α function parameters is available for Mathias-Copeman constants for Soave-Redlich-Kwong (used in PSRK) and for Twu-Bluck-Cunningham-Coon constants (used in VTPR).

The fitting routine supports the simultaneous fit of parameters to vapor pressures, heats of vaporization, second




Figure 38: Start simultaneous fit

virial coefficients, and liquid heat capacities.

The calculation dialog allows

1. selecting or editing the appropriate critical temperature and pressure
2. setting weights for the different properties
3. setting temperature and property ranges (cutting data points)

Tc [K] 562.90 (STOFF) ▾ Pc [kPa] 4417.8 (STOFF) ▾

Vapor Pressure Points	Ref's	Temperature Range	Dependent Value Range	Weight
[]	[]	86.3 191.05	[] 5.93285 4667.33 []	[] 1 []

4. selecting the objective function with regard to the pressure (logarithmic or not) and with regard to all properties (quadratic or linear)
5. selecting the optimization routine (Simplex-Nelder-Mead or Levenberg-Marquardt)
6. plotting the calculated properties together with experimental data from the PCPDDB.

The found parameters can be stored in the public (from DDBST) or private data bank (for custom parameters).

Fit		
0.583254 -0.806032 1.58638		
<input checked="" type="checkbox"/> Logarithmic P <input checked="" type="checkbox"/> Quadratic OF Fit by <input checked="" type="radio"/> SNM <input type="radio"/> LM		
<input type="button" value="Save (Private DDB)"/>	<input type="button" value="Save (Public DDB)"/>	<input type="button" value="Fit"/>




Figure 39: Settings for simultaneous fitting